



## OAK CHEVRON DARK BROWN

The richly smoked finish on this ready-to-install, patterned oak board from the Chevron Collection enhances its deeply burnished hue, and brings a modern expression to its traditional look. Each board is carefully brushed to bring out the natural character of the grain and highlight the texture of the wood. Partial handcrafting gives each board its unique appearance, while micro-bevelling enhances the iconic geometric design. A package contains an even split of left and right hand sided Chevron patterned boards. This product requires an, after installation, maintenance treatment using Kährs Satin Oil Matt.

### PRODUCT DETAILS

<b>Article Number</b>	151XADEKWFKW180
<b>Surface treatment</b>	Oil This floor should be oiled immediately after installation.
<b>Design features</b>	Bevelled 4-sided, Brushed, Smoked
<b>Dimensions</b>	1848 x 305 x 15 mm
<b>Weight per Package</b>	20.01 kg
<b>Area per Package</b>	2.04 m <sup>2</sup>
<b>Area Per Board</b>	0.51 m <sup>2</sup>
<b>Package info</b>	Packages may contain start and stop boards.

### DETAIL DESCRIPTION

Naturally occurring wood colour variations allowed, from light to dark brown. The product includes medium sound and black knots. Knots may vary in size and numbers.

### COLOUR CHANGE

Smoked product - noticeable color change over time.

### FACTS

<b>Wood Species</b>	Oak
<b>Board</b>	Pattern
<b>Grading</b>	Lively
<b>Range</b>	Kährs ID
<b>Collection</b>	Chevron Collection
<b>Resandable</b>	2-3 times
<b>Natural/Stained</b>	Stained
<b>Brinell Value</b>	3,7
<b>Joint</b>	Tongue & Groove
<b>Floor heating</b>	Yes
<b>Warranty</b>	30 years
<b>Wear-layer material</b>	Hardwood
<b>Wear-layer thickness</b>	3.5 mm
<b>Core material</b>	Poplar
<b>Thickness</b>	15 mm
<b>Surface Colour</b>	Dark brown

### TECHNICAL PROPERTIES

<b>Moisture content</b>	EN13183	7%±2%
<b>Minimum Mean Density kg/m<sup>3</sup></b>	>500 kg/m <sup>3</sup>	
<b>Reaction To Fire</b>	EN13501-1	Dfl-s1
<b>Formaldehyde Emission</b>	EN717-1	E1
<b>Content PCP</b>	CEN/TR14823	≤ 5 x 10 <sup>-6</sup> n
<b>Breaking Strength N/mm<sup>2</sup></b>	EN1533	NPD
<b>Thermal Conductivity</b>	EN12664	0,14 W/mK
<b>Thermal Resistance R-Value</b>	.11 (m <sup>2</sup> K/W)	
<b>Biological Durability</b>	EN350-2	Class 1
<b>CARB2</b>	Compliant	



**Descriptions & Imagery**

*All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.*